



CARPEX II

CARPET EXTRACTION CLEANER

DESIGN FEATURES

- Special blend of ingredients to break down embedded soils and lift them into solution. An ultra-cleaner concentrate that gives excellent soil removal when used in steam, hot or cold-water extractor carpet cleaning equipment.
- Designed with the truck mount commercial unit with normal dilution ratio of 4oz. per gallon of water, making Carplex II one of the most cost-effective extraction cleaners available.
- No sticky residues left after cleaning; will not cause resoiling!
- For use on: wool, synthetic, nylon, acrylic, polyolefin and polyester fibers.
- Low to no foam.
- Retards resoiling. No sticky residues left after cleaning.

PROFESSIONAL RECOMMENDATIONS

- Use at 2-4oz. per gallon water, unless carpet area is extremely soiled
- Carplex II can be diluted and used as a pre-spray/spotter at 4oz.per gallon (32:1).
- Overlap your cleaning passes to assure uniform cleaning.
- Pre-treat your spots and agitate with manual brush or use a cylindrical powered port-a-scrub unit.
- Allow enough dry time for carpet, use blowers or fans where appropriate to aid dry time.
- Can be used with microfiber carpet pads for spin cleaning (low moisture), wet surface area and carpet at normal 2-3 oz. per gallon dilution. Rinse pads and re-use during process.

APPLICATION

Commercial/residential carpet extraction cleaner concentrate. Designed for use at 2-3oz. concentrate per gallon water to a maximum of 6oz. per gallon.

SPECIFICATIONS

- Appearance: clear liquid
- Odor: Fresh
- Density (lbs/gal) (± 0.1 @20o C): 8.4
- pH (CONC.) (± 0.5): 9-10
- Flashpoint (TCC): none
- Foam generation: low
- Solubility in Water: Complete
- Stability (40o – 120oF): stable
- Freeze/thaw stability: Ok, 3 cycles
- Shelf life (closed containers, 40o – 120oF): 1 year

ITEM # 150220-24 packed: 4x1g; 2x2.5g; 55g

DIRECTIONS

- Dilute according to soil levels:
 - Heavy soil – 20:1 (6 oz./gallon)
 - Moderate soil – 32:1 (4 oz./gallon)
 - Light soil – 64:1 (2oz./gallon)
- Vacuum floor well.
- Apply pre-treat spray and agitate.
- Pre-spray heavily soiled areas.
- Extract according to directions, do not over wet carpet.
- Allow carpet to dry completely before allowing traffic back on; air movers can be used to speed the drying process.

Always read SDS sheets prior to use and wear safety equipment recommended.

PioneerBrite, Inc. • 1381 Heistan Place • Memphis, TN 38104
Phone: 1-800-783-7320 • Fax: 901-725-7697 • Email: info@pioneerbrite.com

www.PioneerBrite.com